MULTI-PURPOSE SORTING GRAB **MINI-BLUE**





The Mini-Blue: No need for lubrication*, just a pinch of genius!

A versatile range without the need for lubrication* for your material handling.

Mini-Blue sorting grabs excel in many handling areas: branches, curbs, small tree trunks, sand, rocks and many other materials for mini-excavators from 0.8 to 6 tons.

ΝЕи

The Mini-Blue range consists of four models of grabs, each suitable for different wearers.



The new Mini-Blue grabs have many advantages:

- Self-lubricating rings: no lubrication is required on the
 The optimized weight of the grab makes it safe, stable frame, the cylinder, the rod and the shells.
- carried out on a weekly basis. (as part of daily use)
- increasing the strength of the shells.
- A 360° hydraulic rotation designed to adapt to all load- A notched system at the bottom of the shells allows the bearing torques up to 6t.

- and pleasant to use for the excavator operator.
- The two-point lubrication system on the rotation is The double-acting cylinder and the design of the shells make it possible to maximize the effort on the blade.
- The beams of the shells are monobloc cast steel The holding force of the shells allows safe handling of materials.
 - capture of wood or stones.
- The V-shaped design of the frame allows both to A reversible counter blade set made of 500 HB steel increase the volume capacity of the grab and to protect is mounted on the standard clamps, thus extending their the cylinder system.








service life.



*Except on rotation

Technical characteristics



| tonne | Reference | KG * | Volume _{litre} | A mm | B mm | C mm | D mm | E mm | F mm |
|-----------|-----------|------|----------------------------|---------|---------|---------|---------|---------|---------|
| 0,8 - 1,2 | S080G | 73 | 21 | 340 | 620 | 282 | 629 | 632 | 527 |
| 1,2 - 2,2 | S100G | 93 | 30 | 340 | 700 | 317 | 627 | 635 | 605 |
| 2,2 - 3,5 | S230G | 205 | 78 | 440 | 1150 | 334 | 695 | 785 | 764 |
| 3,5 - 6 | S250G | 209 | 78 | 440 | 1150 | 332 | 695 | 785 | 764 |

*Without topplate

Options

- recovery of specific materials thanks to the installation of solid sides and bottoms. The bolted assembly is easily carried out on 🕒 Interchangeable teeth for use in the pierced parts.
- A closure kit allows the A safety valve preventing the opening of the shells is available for added safety.
 - earthmoving.

Documentation and video **Mini-Blue**



A closure kit

()

